

Project Report

Design, Development and Fabrication of Automatically Operated Wheelchair cum Bed

Submitted by

JAISON JOSE(1SJ08ME121)

SUDHAKAR REDDY(1SJ08ME103)

RAKESH R.K (1SJ08ME088)

N KARTHIK (1SJ08ME065)

Project Work carried out at

B G S R&D Centre

S.J.C. Institute of Technology, Chickballapur-562101

Under the guidance of

Internal Guide

B.M.YATHISH KUMARLECTURERDepartment of Mechanical Engineering

S.J.C.I.T. Chickaballapur-562101



Department of Mechanical Engineering

S.J.C Institute of Technology

Chickballapur-562101

Karnataka

2011-2012

TABLE OF CONTENTS

Chapter No:	Contents	page No:
	Certificate	II
	Acknowledgment	III
	Contents	IV
	List of figures	V
1	INTRODUCTION	1
	1.1 Justification	2
	1.2 Objectives	3
2	REVIEW OF LITERATURE	4
	2.1 Ferine et al (2001)	4
	2.2 Jerideau (1996)	4
	2.3 Weiss (1997)	4
	2.4 Dimatteo (1987)	5
	2.5 Smith (1999)	5
	2.6 Patrick et al (2004)	5
	2.7 Earls (1991)	5
	2.8 Martin (2003)	6
	2.9 Hebert et al (1997)	6
	2.10 Shaffer (1988)	6
	2.11 Atimichuk (1986)	7
	2.12 Luther (1994)	7
3	MATERIALS AND METHOD	8
	3.1 Development of Automatic Wheelchair cum Bed	8
	3.2 Design Consideration	11
	3.2.1 Design of Manual Wheelchair used in the study	11
	3.2.2 General Consideration in Wheelchair Design	12
	3.3 Wheelchair Design	13
	3.3.1 Wheelchair Design Principles	13
	3.3.2 Basic Manual Wheelchair Design Parts	15
	3.4 Wheelchair Design Criteria	17
	3.5 Wheelchair Performance	18
	3.6 Wheelchair Evaluation	23
	3.7 Cushion Slings and Solid Seats	25
	3.8 Wheelchair Durability	28

TABLE OF CONTENTS

	3.9 Safe and Reliable Wheelchairs	28
	3.10 Design Consideration of Helical Compression Springs	31
	3.10.1 Spring design and Specification	32
4	Results and Discussion	36
5	Conclusion	37
6	Reference	38

FIGURES

Fig no	TITLE	Page no
1.1	Wheelchair with and without hand rims	2
3.1	Conventional wheelchair	8
3.2	Automatic wheelchair	10
3.3	Automatic wheelchair cum bed	10
3.4	Wheelchair cum bed mechanism	11
3.5	Conventional wheelchair parts	14
3.6	Wheelchair ant-tip wheels	19
3.7	Wheelchair with and without camber	20